



Micro Commercial Components 130 W Cochran St, Unit B Simi Valley, CA 93065 USA Tel:818-701-4933 MD36A08D1 MD36A12D1 MD36A16D1 MD36A18D1


Features

- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information)
- Blocking Voltage:800 to 1800V
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- · Glass passivated chip


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- · Field supply for DC motors





36 Amp GLASS PASSIVATED RECTIFIER DIODE MODULES 800~1800 Volts



		DIMEN	SIONS			
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX	NOTE	
Α	0.768	0.807	19.50	20.50		
В	1.161	1.201	29.50	30.50		
С	0.335	0.374	8.50	9.50		
D	0.315	0.354	8.00	9.00		
Е	0.594	0.630	15.10	16.00		
F	0.217	0.256	5.50	6.50		
G	0.531	0.571	13.50	14.50		
Н	0.650	0.689	16.50	17.50		
I	3.130	3.169	79.50	80.50		
J	3.642	3.681	92.50	93.50		
K	0.256		6.50		Ф	
L	0.413	0.453	10.50	11.50		
М	0.807	0.846	20.50	21.50		



Module Type

TYPE	VRRM	Vrsm
MD36A08D1	800V	900V
MD36A12D1	1200V	1300V
MD36A16D1	1600V	1700V
MD36A18D1	1800V	1900V

Maximum Ratings

Symbol	Conditions	Values	Units
I FAV	Single phase ,half wave 180° conduction Tc=104℃	36	А
I _{FSM}	t=10mS Tvj =45℃	650	А
i ² t	t=10mS Tvj =45℃	2100	A ² s
Visol	a.c.50HZ;r.m.s.;1min	3000	V
Tvj		-40 to +150	${\mathbb C}$
Tstg		-40 to +125	${\mathbb C}$
Mt	To terminals(M5)	3±15%	Nm
Ms	To heatsink(M6)	5±15%	Nm
Weight	Module (Approximately)	100	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Per diode	1.0	°C/W
Rth(c-s)	Module	0.1	°C/W

Electrical Characteristics

Cumbal	Conditions	Values			Unito
Symbol		Min.	Тур.	Max.	Units
$V_{\sf FM}$	T=25°C I _F =100A	_	1.25	1.40	V
I _{RD}	Tvj=150°C V _{RD} =V _{RRM}	_	_	5	mA



Performance Curves




Fig1. Power dissipation




Fig3. Transient thermal impedance




Fig5. Forward Characteristics




Fig2.Forward Current Derating Curve




Fig4. Max Non-Repetitive Forward Surge Current



Ordering Information:

Device	Packing
Part Number-BP	Bulk: 10PCS/BOX;100PCS/CTN

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.