TGBWP, T and BMT Series

TGBWP Series

1-1/8"-18 thread; trunk/hood groove bracket mount

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*	Cable Exit Angle	Туре
TGBWP45C-NC	17′	RG-58/U	None	45°	N/A
TGBWP45PL	17′	RG-58/U	Mini-UHF	45°	Crimp
TGBWP45FFME	17′	RG-58/U	Female FME*	45°	Crimp



CTEL®

TGBWP45

T Series

1-1/8"-18 thread mount; trunk lid mount

NDARD CONFIGURATION						
Model	Length of Coax	Coax	Connector*	Туре		
TTT	NA	None	None	N/A		
T-NC	17′	RG-58A/U	None	N/A		
TC-NC	17′	RG-58/U	None	N/A		
Т	17′	RG-58A/U	PL259	Solder		
тс	17′	RG-58/U	TNC	Crimp		
TPL	17′	RG-58/U	Mini-UHF	Crimp		

BMT Series

Black 1-1/8"-18 thread; all metal trunk lid mount; 17' RG-58/U or RG-58A//U cable options. For other cable lengths and connector configuration options, contact PCTEL Customer Service.



BMT

* Connectors are shipped loose. Connectors may be attached upon request for an additional charge. For other connector options, please refer to the Mobile Antenna Mounts Configurator Part Number Guide.