

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX



Features:

- Small form factor
- PCB size W x L x H (with adhesive): 40 [1.57] x 15 [0.59] x 0.7[0.028]mm [inch]
- Lead free materials
- RoHS Compliant Product
- · Mounting with adhesive tape
- · Various cable lengths available
- Connector options:
- Hirose connector U.FL-series (I.PEX connector MHF-series compatible)
- MMCX right angle jack (male)
- Sunridge MCD series connector

Applications:

- Penta band EU/US GSM/WCDMA
- Frequency range: 850 / 900 / 1800 / 1900/ 2100 MHz
- 824-960MHz/1710-2170MHz

All dimensions are in mm / inches

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA

Tel:1-858-674-8100

Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



1



Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

This document covers all product variants of the following product family:

P/N	Cable length (mm/inch)	Connector	P/N	Cable length (mm/inch)	Connector
W3538B0035	35/1.38	U.FL	W3538E0300	300/11.81	MMCX
W3538B0045	45/1.77	U.FL	W3538T0150	150/5.91	MCD
W3538B0075	75/2.95	U.FL	W3538T0200	200/7.87	MCD
W3538B0085	85/3.35	U.FL	W3538T0300	300/11.81	MCD
W3538B0100	100/3.94	U.FL	W3538M0085	85/3.35	Murata
W3538B0150	150/5.91	U.FL	W3538M0150	150/5.91	Murata
W3538B0200	200/7.87	U.FL	W3538M0200	200/7.87	Murata
W3538B0300	300/11.81	U.FL	W3538M0300	300/11.81	Murata
W3538E0075	75/2.95	MMCX	W3538G0500	500/19.69	SMA
W3538E0150	150/5.91	MMCX	W3538A0200	200/7.87	N/A
W3538E0200	200/7.87	MMCX			

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100

Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



2



Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

ELECTRICAL SPECIFICATIONS

Typical free space performance, measured in test unit mechanics(position 1).

Cable Length (mm)	P/N	Frequency Range(MHz)	Max Gain (dBi)	Efficiency (%)	Return Loss min(dB)
		824-960	-1.2	27	-4
35	W3538B0035	1710-1990	1.0	33	-7
		1920-2170	1.1	40	-4
		824-960	0.78	44	-3
45	45 W3538B0045	1710-1990	1.73	49	-5
		1920-2170	1.84	50	-5
		824-960	-1.64	30	-3
75	W3538B0075	1710-1990	2.26	53	-6
		1920-2170	2.37	55	-6
		824-960	0 -2.38 25 -3	-3	
85	W3538B0085	1710-1990	2.3	57	-6
		1920-2170	1.96	58	-6
		824-960	-1.77	14	-3
100	W3538B0100 1710-1990	1710-1990	2.55	40	-6
		1920-2170	2.89	47	-6

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION



This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.



3



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

ELECTRICAL SPECIFICATIONS

Cable Length (mm)	P/N	Frequency Range(MHz)	Max Gain (dBi)	Efficiency (%)	Return Loss min. (dB)
	W3538B0150	824 - 960	-1.05	37	-3
150	W3538E0150 W3538T0150	1710 - 1990	2.27	47	-6
	W3538M0150	1920 - 2170	2.04	53	-6
	W3538B0200	824 - 960	0.53	40	-6
200	W3538E0200 W3538T0200	1710 - 1990	4.18	56	-6
	W3538M0200 W3538A0200	1920 - 2170	4.06	57	-6
	W3538B0300	824 - 960	2.40	42	-6
300	W3538E0300 W3538T0300	1710 - 1990	3.21	45	-6
		1920 - 2170	2.68	44	-6
		824 - 960	1.61	30	-5
500	00 W3538G0500	1710 - 1990	3.10	47	-6
		1920 - 2170	2.78	44	-6

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION



4



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

MECHANICAL SPECIFICATIONS

PCB size 40 [1.57] x 15 [0.59] x	0.7[0.028](with adhesive) mm[inch]
Connector type	Optional
Cable type	Optional
Cable length	Optional

ENVIRONMENTAL SPECIFICATIONS				
Operating Temperature	-40/+85	° C		
Storage Temperature	-40/+85	° C		
RoHS Compliant		Yes		

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



5



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

OTHER SPECIFICATIONS

Cable and Connector Configuration

Antenna feed cable:

1.13mm OD with Hirose connector (U.FL series, MHF compatible)

1.13mm OD with MMCX right angle jack (male)

0.81mm OD with Murata GSC connector

0.81mm OD with Sunridge MCD connector

1.13mm OD with SMA male connector

Hirose U.FL connector

r MMCX right angle jack (male)

SMA male connector



Murata GSC connector



In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Issue: 1942





6



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

MECHANICAL DRAWING



Dimension unit is mm

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



7



Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

TEST SETUP

Test Unit and Antenna Mounting Options

Test unit is illustrative and antenna does not need effective ground plane

Position 1. Antenna could be mounted at same plane and level as device board or a different level also



Position 2. Antenna could be mounted on upright position at bottom end of device



Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

TEST SETUP

Position 3. Antenna could be mounted on upright position at long edge of device



Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



9



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

TECHNICAL DATA SHEET

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION





Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 11



Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

TECHNICAL DATA SHEET

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

12



Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 13



Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



14



Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



15



Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



17



Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

CHARTS



Note: Antenna tested on 2mm plastic plate with 200mm feed cable.

Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Description: 824-960/1710-2170MHz 2G/3G Pentaband PCB antenna with coax feed

Series: Internal PCB Antenna PART NUMBER: W3538XXXXX

PACKAGING

10PCS/PE bag 10PE bag/foam bag 10 foam bag/ carton box Total 1000PCS/carton box



Issue: 1942

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

