


Features

- Broadband operation 20 - 512MHz
- Output power: 30 W Min
- Power gain: 8.0 dB Min
- Rugged push-pull FET
- External bias control
- Rugged construction for extreme environments
- Suitable for most commercial and industrial applications

Absolute Maximum Ratings

Parameter	Rating	Units
Supply Voltage	30	V
Input Power	8	W
Output Power	120	W
Bias Current	6.5	A
Operating Case Temperature	-40 to +85	°C
Storage Temperature	-50 to +100	°C

Product Image



Electrical Specifications: $T_c = 25 \pm 5 \text{ }^\circ\text{C}$

Parameter	Test Conditions	Min	Typ	Max	Units
Frequency Band	$V_{SUPP} = 28 \text{ V}$, $P_{OUT} = 20 \text{ watt}$	20	-	512	MHz
P_{1dB}	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$	30	40	-	W
Power Gain	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$	8.0	-	-	dB
Efficiency	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$, $P_{OUT} = 40 \text{ W}$	-	37	-	%
Gain Variation With Frequency	$V_{SUPP} = 28 \text{ V}$, $P_{OUT} = 4 \text{ W}$	-	-	± 2.5	dB
Input VSWR	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$	-	3.5:1	-	VSWR
Load Mismatch Tolerance	$V_{SUPP} = 28 \text{ V}$, $F = 512 \text{ Mhz}$, $P_{OUT} = 20 \text{ W}$	-	5:1	-	VSWR
Even Harmonics	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$, $P_{OUT} = 20 \text{ W}$	-	-	-25	dBc
Odd Harmonics	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$, $P_{OUT} = 20 \text{ W}$	-	-	-15	dBc
Spurious Output	$V_{SUPP} = 28 \text{ V}$, $I_D = 400 \text{ mA}$, $P_{OUT} = 20 \text{ W}$	-	-	-60	dBc
IP3	$V_{SUPP} = 28 \text{ V}$, $P_{OUT} = 20 \text{ W}$, $\Delta F = 100 \text{ kHz}$	-	56	-	dBm

ADVANCED: Data Sheets contain information regarding a product M/A-COM is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.



PRELIMINARY: Data Sheets contain information regarding a product M/A-COM has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Outline Drawing



Nickel Plated Copper Housing

PIN FUNCTION			
PIN(S)	Function	PIN(S)	Function
1, 4, 7	Ground	5	Vdc Input
2	RF Input	6	RF Output
3	Vbias		